



JUST ADD WATER



20 kg

Render It™ MULTISURFACE GREY

Excellent flexibility & adhesion
Suitable for masonry, styrene, fibre cement sheets & AAC blocks
Easy to apply one part render
Hand mix (no drill required)
Covers approx 2.5m² per 20kg bag (5mm thickness)



for masonry surfaces, styrene,
fibre cement sheets, AAC blocks

RENDER IT

- ✓ Premixed easy to use product produced to trade standard
- ✓ No primer or curing compound is required
- ✓ Suitable for both internal and external use
- ✓ Excellent bond strength and adhesion to masonry, styrene, fibre cement sheets and AAC block surfaces.
- ✓ Can be coloured with oxides for a paint-free finish

Build with Confidence

cementaustralia.com.au or call 1300 CEMENT (1300 236 368)





**MULTISURFACE
RENDER**

Cement Australia grey cement based 'Render It™ Multisurface' is an easy to use Polymer Modified Render which only requires the addition of clean water and thorough mixing before application.

This product incorporates additives that enable this one part render system to be easily applied in thicknesses ranging from 2mm to 10mm in a single application.

Render It™ Multisurface Grey can be applied to masonry, styrene, fibre cement sheets and AAC blocks.

HOW TO USE



STEP 1 Prepare surface by removing any loose materials with a brush.



STEP 2 Add clean water as directed on the bag into a bucket or wheelbarrow and pour one bag of Render It™ into the water.



STEP 3 Mix thoroughly to a creamy, lump-free consistency. Let the mix stand for 5 minutes before applying.



STEP 4 Apply the render with a steel trowel in an upward motion from left to right (or opposite for left-handed application), ensuring the render is applied in a consistent thickness. Allow render to become firm and finish off with a wooden trowel or polystyrene float.

Keep render damp for 24 hours with a fine water spray or by covering the surface with plastic or damp hessian.

COVERAGE

One 20kg bag of Render It™ will cover approximately 2.5m² at 5mm thickness.

HOW MUCH DO I NEED?

Visit cementaustralia.com.au/calculators to use our handy product calculator to work out how much Render It™ you need for your project.

LIMITATIONS

Render It™ should not be applied in full sun.

To view all product limitations, storage & handling tips please visit cementaustralia.com.au

Item Code 15273

Cement Australia
Render It 20kg



PRODUCT DISCLAIMER

Recommendations regarding the use of this product are to be taken as a guide only. If in doubt contact Cement Australia Pty Limited ("Cement Australia") or seek professional advice. To the extent permitted by law, Cement Australia excludes all implied warranties, conditions and guarantees imposed by legislation. Cement Australia excludes all liability for loss, damage or injury arising from use of the product (i) otherwise than in accordance with the recommendations or (ii) for purposes other than those for which it is ordinarily acquired. For all other loss, damage or injury arising from the use of this product, to the extent permitted by law Cement Australia's liability is limited, at its discretion, to refunding the cost of the product or resupplying the product or equivalent product.

Safety Data Sheet available at cementaustralia.com.au

MADE
Right Here

**CEMENT
AUSTRALIA**®